

Assessment Of Degradative Potentials Of Bacteria Isolated From Palm Oil-Polluted Site Using Spectrophotometric Method

¹Nwakoby Nnamdi Enoch, ²Ejimofofor Chiamaka Frances, ³Ikechukwu Harmony Iheukwumere, ⁴Ezeogo James Item and ⁵Abba Oluchukwu

^{1,3}Department of Microbiology, Chukwuemeka Odumegwu Ojukwu University Uli, Anambra State, Nigeria.

²Department of Biological Science, Chukwuemeka Odumegwu Ojukwu University Uli, Anambra State, Nigeria.

⁴Department of Science Laboratory Technology, Federal Polytechnic Ngodo Isuochi, Abia State, Nigeria.

⁵ Department of Microbiology, Federal University Gusau, Zamfara State, Nigeria.

DOI: <https://doi.org/10.51244/IJRSI.2025.120800306>

Received: 02 Sep 2025; Accepted: 08 Sep 2025; Published: 08 October 2025

ABSTRACT

Bioremediation is one of the current approaches in environmental microbiology or environmental biotechnology that has been exercised for the reduction and removal of hydrocarbon pollutants. Microorganisms, typically bacteria that have particular metabolic capacities, are essential for the biodegradation of hydrocarbon pollutants. This study was undertaken to assess *ex situ* degradative potentials of *Pseudomonas* species isolated from palm oil effluent-polluted site using spectrophotometric method. Soil sediments were collected from different points at palm oil effluent disposal site located at different local palm oil producers at Uli community, Ihiala Local Government, Anambra State. The samples were analyzed for the presence of palm oil effluent degrading bacteria using a modified mineral basal medium. The bacterial isolates were characterized based on their cultural characteristics, microscopy, and biochemical characteristics. The hydrocarbon adaptation utilization potentials of the bacterial isolates were evaluated using spectrophotometric method. The biodegradative potentials of the bacterial isolates were evaluated using hydrocarbon supplemented modified mineral basal medium and spectrophotometer. The Gram negative bacteria isolated were *Pseudomonas* species. The optical diameter of the adapted bacterial isolates showed that the isolates adapted to the hydrocarbon medium while the biodegradative potentials of the isolates showed that the hydrocarbon was biodegraded as revealed in the weight loss, which increased as the day of degradation increased. The study has shown that *Pseudomonas* species are good hydrocarbon utilizing bacteria, which can be optimized in bioremediation of palm oil effluent-polluted site.

Keywords: Palm oil, effluent, Bacteria, degradation

INTRODUCTION

Palm oil mill effluent (POME) which is also known as Palm oil effluent (POE), Palm oil slurry (POS) or Palm oil sludge (POS) is a perennial crop with the most common species “*Elaeis guineensis*” grown extensively in West Africa's humid tropical and subtropical region, where it originated from (Bambang et al., 2012), however the world's largest producers of crude palm oil are actually Indonesia, Malaysia, Thailand, Columbia and Nigeria (Ohimain and Izah, 2014; Izah et al., 2016). Among all territorial name been given, Palm oil mill effluent seems to summarize it's content which is defined as the voluminous liquid waste that originates from the sterilization and clarification forms in milling oil palm. It is a wastewater produced from palm oil milling exercises which require successful treatment before release into nature because of its exceptionally polluting properties (Ismail et al., 2010).

Thus, POME is being treated via palm oil mills before evacuating it into the streams and rivers. Palm oil mill effluent is termed to be a highly polluting material and researchers have done so much in their studies to find ways of removing its threat to the environment (Awotoye *et al.*, 2011; Izah and Ohimain, 2016). The

composition of the effluents are from different sources and are obtained from palm oil, water, sand and solid (suspended and dissolved). Water which composed of 93-95%, solidly composed of 3- 4% and oil composed of 0.5-2% are various composition as a percentage of total sludge (Madaki *et al.*, 2013). Biodegradation also known as “biological breakdown” is the process by which organic substances are decomposed by microorganisms (mainly aerobic bacteria) into simpler substances such as carbon dioxide, water and ammonia. The use of biotechnological forms including microorganisms, with the target of taking care of environmental contamination issues, is quickly developing where POME and its side effects are concerned. The process by which microorganisms such as bacteria, fungi and other biological activity act on material by naturally disintegration is called Biodegradation. The biological treatment relies immensely upon a consortium of microorganism's activities, which operate the organic substances present in the POME as enhancements and in the end debase these organic issues into a simple by-product, for example, methane, carbon dioxide and hydrogen provided, and water (Mohammadreza and Soheila, 2014).

According to Liew *et al.* (2015), the past few decades, various methods have been recorded for the treatment of POME. Anaerobic or facultative ponding method, tank digestion and mechanical aeration, tank digestion and facultative ponds, physico-chemical and biological care, and decanter and facultative ponds are the most refined treatment plans that have been widely applied in POME degradation. However, these approaches have some disadvantages, such as the prolonged period of retention, greenhouse gases output, large land area requirement and inconsistent nutrient removal (Ganapathy *et al.*, 2019; Affandi *et al.*, 2014).

Biological treatment such as ponding system is a conventional treatment that involves aerobic and anaerobic processes which involves microorganisms such as bacteria, molds, algae, yeasts, and fungi to degrade lipids in the POME (Ganapathy *et al.*, 2019; Rupani, *et al.*, 2019). One of the unique ways through which microorganisms obtained energy is by catalyzing energy that causes chemical reactions involving breaking bonds and moving electrons away from the pollutants, during this process, the organic contaminant is oxidized in this form of reaction, while the chemical that acquires the electron is reduced.

Several researchers had succeeded in isolating and characterization of bacteria and fungi from palm oil effluent-contaminated soil (Kwute and Ijah, 2014; Adegbola *et al.*, 2020; Popoola *et al.*, 2022). Some of the microorganisms identified were *Bacillus*, *Pseudomonas*, *Micrococcus*, *Aspergillus*, *Penicillium* and so on. These microorganisms survived in such environment due to their high degradative potentials. The energy obtained from this transition is then invested in growth and metabolism of the biodegrading microbe (Ramadan *et al.*, 2012; Loretta *et al.*, 2016). The aim of this study is to assess an *ex situ* degradative potentials of *Pseudomonas* species isolated from palm oil-polluted site using spectrophotometric method.

MATERIALS AND METHODS

Study Area

The study was conducted at Umuaku, Uli, Ihiala Local Government Area, Anambra State. Uli is a village located between latitudes 5.47°N and 5.783°N and longitude 6.52°E and 6.87°E on the South eastern part of Nigeria. Uli extends westward to the confluence of the rivers of Atammiri and Eyinja, and across Usham lake down to the lower Niger region. Uli has rainforest vegetation with two seasonal climatic conditions: rainy season and dry season, which is characterized by the harmattan between December and February. Uli is characterized by double maxima of rainfall with a light drop in either July or August known as dry spell or August break. The annual total rainfall is about 1,600 mm with a relative humidity of 80 % at dawn.

Sample Collection

The soil surface was carefully scrapped out using sterile spoon. Soil auger was used to a plough depth of 15 cm in the sampling sites (palm oil effluent-contaminated sites), and soil sample was drawn (up to 10 samples) from each sampling unit into a sterile tray. The samples were thoroughly mixed and foreign materials such as roots, stones, pebbles and gravels were carefully removed. The soil sample was then reduced to half by quartering the sample. Quartering was carried out by dividing the soil sample into four equal parts and the two opposite quarters were discarded and the remaining two quarters were mixed. The process was repeated for

the rest of soil samples used for this study. The samples were carefully labeled and then kept in a disinfected cooler, to maintain its temperature and stability of the number of the isolates. The samples were transported to the laboratory for analysis within 2 h.

Sterilization of materials

As stated in prescott *et al.* (2005), conical flasks (pyrex), prepared media and other plastic materials were sterilized by autoclaving at 121°C for 15 minutes at a pressure of 15 psi. Glass wares such as pipettes, glass spreader, petri dishes, measuring cylinder, and other glass materials were sterilized in the laboratory hot air oven at a temperature of 160 °C for 1hr before use.

Isolation of Palm Oil Degrading Bacteria from the Samples

Serial dilution

A ten-fold serial dilution of the samples was carried out by adding 1g or 1ml respectively of sediment and water samples aseptically in test tubes containing 9ml of 0.85% of physiological saline solution labeled 10^{-1} to 10^{-10} dilution factors with the aid of a sterile pipette in a repeated manner. With another sterile pipette, 0.1 aliquots of the appropriate dilutions (dilutions that produce colony counts between 30 – 300 colonies) were spread plated on the surfaces of the solidified media in triplicates with the aid of a glass spreader. Precisely, 10^{-3} dilutions were spread plated. The spreader was sterilized after each successive spreading by dipping it in 70% ethanol and then passing it through flame of a Bunsen burner (Bahig *et al.*, 2008; Chikere *et al.*, 2009; Kafilzadeh *et al.*, 2012).

Enrichment, culturing and isolation of palm oil degraders

The palm oil degraders were isolated from sediments of the three sampling sites using modified mineral basal agar (4g K_2HPO_4 , 1.0g $(NH_4)_2SO_4$, 0.1g $MgSO_4$, 1.8g K_2HPO_4 , 0.1g $FeSO_4$, 0.1g NaCl, 0.2ml $CaCl_2$, 15g Agar agar and distilled water 1000ml at pH 7 ± 0.2) enriched with xylene, anthracene and pyrene as hole carbon and energy source. The medium was sterilized by autoclaving at 121°C at a pressure of 15psi for 15 minutes. Thereafter, 0.2 ml acetone solution containing 0.1% w/v of the selected hydrocarbons (xylene, anthracene and pyrene) were aseptically pipetted and uniformly spread on the agar surface of the pre-dried petri dish plates. The acetone was allowed to evaporate under sterile condition before inoculating with 0.1ml of diluted sediment and water samples. The inoculated plates were sealed using adhesive tape and foil to prevent contamination and photolysis and later placed in black polythene bags, and then incubated in the dark at 28 ± 0.2 °C for 24 – 48h (John and Okpokwasili, 2012).

Purification and maintenance of cultures

Colonies that developed on hydrocarbon-coated plates were replicated onto fresh hydrocarbon-coated agar plates and incubated for 14 days. Isolates that grew on these plates were selected as xylene, anthracene and pyrene degraders and sub-cultured on Bjou bottles where they are preserved at 4°C in refrigerator (John *et al.*, 2012).

Cultural and Morphological Characteristics

After sub-culturing and incubation, culturing morphological properties such as shape, elevation, margin, optic, texture, colour, size and surface characteristics of the selected bacterial strains were observed and noted (Prescott *et al.*, 2005).

Gram staining

This technique divides bacteria into Gram positive and Gram negative groups. A smear of the isolates was made on a clean dry grease free slide, using a sterile wire loop. The smear was air dried and heat fixed by passing over flame quickly three times. It was then covered with 0.5% crystal violet solution for 1minute and rinsed with distilled water. The slide was flooded with 1% Gram's iodine (which served as a mordant that

fixes the dye inside the cell). The iodine was washed off after one minute and 95% ethanol was used to decolorize the smear for 15 seconds. The smear was counter stained with 0.1% safranin dye solution for one minute. It was then washed off and the slide air-dried, and observed under the microscope using oil immersion objective lens after placing a drop of oil immersion. Gram positive and negative reactions were indicated by purple and red colors respectively (Cheesbrough, 2010).

Spore staining

According to the method of HPA (2007), smears of the isolates were prepared and fixed on a slide. The underside was vapor heated and flooded with 5% malachite green solution. Heating would continue until visible water condensate forms under the slide with evaporation at the top. It was washed using distilled water. Smears were counter stained with 0.5% safranin solution for 10 seconds. Slides were washed, dried and observed under oil immersion objective lens after placing a drop of immersion oil. A green space within the cells would indicate the presence of spores.

BIOCHEMICAL CHARACTERISTICS

Catalase test

As stated in Cheesbrough (2010), the test identifies organisms that produce the enzyme catalase. A drop of 30% freshly prepared hydrogen peroxide (3ml H₂O₂ in 7ml H₂O) was placed on a clean slide and loopful of isolate was transferred into it and emulsified. The appearance of gas bubbles indicates positive reaction. The reagent was shaken before the test to expel any dissolved oxygen and avoid false positive result.

Indole test

As stated in Cheesbrough (2010), the tryptone-broth was prepared and 5ml was dispensed into each test tubes and sterilized. The isolates were inoculated into the test tube and incubated at 28°C for 48h. After incubation, 5 drops of Kovac's reagent (4 – p – dimethyl – aninobenzaldehyde) were added to the tubes, shaken gently and allowed to settle. A red coloration in alcohol dye indicates a positive result for the reaction.

Motility test

A directional and purposefully movement of the organisms demonstrate motility. Nutrient broth was supplemented with 0.2% agar, dispensed into test tubes and sterilized by autoclaving at 121°C and 15psi for 15minutes. The inoculated test tubes were incubated for 24h. Diffused growth, which spreads throughout the medium, indicates motility. Non-motile organisms grew along the line of inoculation (Cheesbrough, 2010).

Citrate test

As stated in Prescott *et al.* (2005), the test was used to determine organisms that could utilize citrate as a sole-carbon source for metabolism. Slant of Simmon's citrate agar were prepared according to manufacturer's instructions. The slants were inoculated by streaking over the surface with a loopful of an 18h old culture and incubated at 37°C for 48h. Positive results were indicated by the growth on agar and a change in color from green to blue and absence of color change indicates negative results.

Starch hydrolysis test

To determine the abilities of the isolates to hydrolyze starch, 50 µl of liquid cultures of each isolates were dropped on starch – based solid medium containing per litre, 3g meat extract, 10g starch and 15g agar (Cheesebrough, 2010).

Gelatin test

As stated by Prescott *et al.* (2005), gelatin agar medium was composed of 40g/l of gelatin, 30g/l of tryptic soy broth and 100ml of distilled water. A small inocula of the isolates was stabbed to about three-quarter of the

way to the bottom of a tube of deep agar with the inoculating needle. The separate stab tubes for each of isolates were incubated at 37°C for 24 – 48h. The incubated stab and the un-inoculated control tubes were placed into the refrigerator for approximately 30 minutes. The inoculated stab tubes were compared with the control by tapping the tubes gently.

Hydrogen sulfide production test

As stated in Prescott *et al.*(2005), The test determines that ability of organisms to reduce sulfur compounds Triple sugar ion agar slants were prepared and each isolates were inoculated into test tubes by streaking the inocula across the top of the slants and stabbing the slant tubes to the bottom. Tubes were incubated at 28°C for 24h. Positive result is indicated by the formation of black color coupled with displacement of the agar slant and red to yellow color observation.

Sugar fermentation

As stated in Prescott *et al.*(2005), the test determines the ability of the isolates to ferment glucose, sucrose, lactose, mannitol, maltose, xylose, arabinose and saccharose and also ability to produce gas. The fermentation medium contained 1% peptone water and 5 drops of 0.2% bromothymol blue indicator solution. Then 9ml of the medium was dispensed into clean dry test tubes in which Durham tubes been dropped (inverted and without air space) and sterilized by autoclaving at 121°C and 15psi for 15 minutes. 1ml of the sterile 5% test sugar solution was added to medium and inoculated with a loopful of the test organisms and incubated at 30°C for 24h. A change in color of the medium (from blue to yellow) was recorded as positive reaction, while presence of gas in Durham tubes indicates gas production.

Oxidase test

As stated in Prescott *et al.*(2005), the test identifies any organism that produces the enzyme oxidase. A loopful of isolates was transferred into pieces of Whatman No.1 filter paper, impregnated with a solution of freshly prepared oxidase test reagent (N,N,N',N' tetra-methyl-phenylene diamine) and smeared. Oxidation of the phenylene diamine in the reagent to dark purple or blue color within 10 seconds indicates a positive result.

Casein hydrolysis test

The casein hydrolysis was observed by zones of clearing after 24h of incubation. For this purpose, 50 µl liquid cultures of each isolates were dropped on casein-based solid medium containing (per litre) 10 g casein and 15g agar. After 24h of incubation, the inhibition zones were determined (Cheesbrough, 2010).

Hydrocarbon Adaptation Utilization Test

In order to screen and select the best and strongest degrading bacterial isolate, different organisms were tested by growing 5ml of each desired isolates in large test tubes containing 25 ml of the modified mineral basal medium with 1ml of xylene, anthracene and pyrene hydrocarbons which were dissolved in acetone and added to each tube autoclaving. Thereafter, the test tubes were incubated at room temperature (28±2°C) for five days. Bacteria that started growing fast with high turbidity in the vicinity of the medium containing aromatic compounds measured at 600nm using a UV – VIS spectrophotometer (Astell, UV – Vis Grating, 752W) were selected as the candidate of xylene, anthracene and pyrene degrading bacteria. Cultures without increase in turbidity over initial optical density (OD) and uninoculated control were scored as no growth (-) while cultures with increased turbidity significantly greater than the control were scored as growth (+) (John *et al.*, 2012).

Degradation Assay

By adopting the methods of Bennet *et al.* (2012) and John and Okpokwasili (2012), as modified in this study, the degradation rates of bacterial isolates were determined using hydrocarbon supplemented modified mineral

basal medium (4g K₂HPO₄, 1.0g (NH₄)₂SO₄, 0.1g MgSO₄, 1.8g K₂HPO₄, 0.1g FeSO₄, 0.1g NaCl, 0.2ml CaCl₂, 15g Agar agar and distilled water 1000ml at pH 7±0.2). Precisely, 1ml of 48 h old cultures of each organisms were introduced into 28 sterile 200ml capacity conical flasks (7 sets of 4 flasks) containing 100ml of sterile modified mineral basal medium supplemented with 1 ml of xylene or 1ml of anthracene or 1g of pyrene, respectively as source of carbon at 24°C for 24 days. During incubation, representative samples from the three days sets of flasks were withdrawn at intervals of 0, 4, 8, 12, 16, 20 and 24 days and the residual hydrocarbons were determined spectrophotometrically using ethyl acetate as the extraction solvent. For each sample, 5 ml

ethyl acetate was added and vigorously shaken manually. The organic and aqueous layers from media were separated by centrifugation at 5000rpm for 20 minutes. The aqueous layers were discarded while the organic layers were analyzed with UV – VIS spectrophotometer at 240 nm wavelength (Astall UV – Vis Grating, 752 W). The percentages of biodegradation of the hydrocarbons were determined as follows:

$$\% \text{ degradation} = \frac{a-b}{a} \times \frac{100}{1}$$

Where a = the absorbance of the medium before incubation; b is the maximum absorbance of the medium after each 4th day of the incubation period.

Statistical Analysis

The difference in the absorbance of the bacterial isolates was determined using students' 't' test and values of P that exceeded 0.05 (P > 0.05) were considered not significant.

RESULTS

Characterization of Bacterial Isolates in the Impacted Soil

The result of characterization of the bacterial isolates in the impacted soil is presented in Table 1. The result revealed that the bacterial isolate Y appeared cream white on Nutrient agar while isolate Y appeared fussy white on the same agar. The edge, elevation, surface, optical nature, and size of the isolates appeared entire, convex, smooth, opaque, and small, respectively. Both isolates were Gram negative, motile, rods, and non-spore formers. The biochemical characteristics of the isolates revealed that both isolates were positive to catalase, citrate, oxidase, gelatin, casein, starch, and glucose, while maltose and sugar alcohols were not utilized.

Table 1: Cultural and morphological characteristics of the bacterial isolates

Parameter	Isolate X	Isolate Y
Appearance on Nutrient Agar	Pale yellow	Pale green
Edge	Entire	Entire
Elevation	Convex	Convex
Surface	Smooth	Smooth
Optical Nature	Opaque	Opaque
Size	Small	Small
Gram Reaction	Negative	Negative
Cell Morphology	Rods	Rods
Motility	Motile	Motile
Endospore	Absent	Absent

Bacterium	<i>Pseudomonas</i> species	<i>Pseudomonas</i> species
-----------	----------------------------	----------------------------

Table 2: Biochemical characterization of the bacterial isolates

Parameter	Isolate X	Isolate Y
Catalase	+	+
Citrate	+	+
Indole	–	–
Oxidase	+	–
H ₂ S	–	–
Gelatin	+	+
Casein	+	+
Starch	+	+
Glucose	+	+
Maltose	–	–
Dulcitol	–	–
Inositol	–	–
Xylitol	–	–
Bacterium	<i>Pseudomonas</i> sp.	<i>Pseudomonas</i> sp.

Optical Diameter of the Adapted Isolates and Weight Loss of hydrocarbon During Degradation

The result of optical diameter of the adapted isolates is presented in Table 3. The result revealed that at day 0, the bacterial isolates recorded the least optical diameter of 0.0021 and 0.0039, respectively. Meanwhile, as the day progresses, the optical diameter increased but the increment was not significant. Meanwhile, isolate Y showed higher optical diameter as the day increased. Similarly, the weight loss of hydrocarbon during degradation is presented in Table 4. The result revealed that at day 0, there was zero weight loss. Also, the weight loss during degradation increases as the day increases with the highest weight loss recorded at day 4 of degradation.

Table 3: Optical diameter of the adapted isolates

Day	<i>Pseudomonas</i> X	<i>Pseudomonas</i> Y
0	0.0021	0.0039
1	0.0282	0.0377

2	0.0562	0.084
3	0.1310	0.1960
4	0.2520	0.3900

Table 4: Weight loss of the hydrocarbon during degradation

Day	Weight (%) Pseudomonas X	Pseudomonas Y
0	0.00	0.00
1	0.58	0.69
2	0.95	1.91
3	2.53	2.98
4	3.97	4.95

DISCUSSION

Environmental contamination has threatened the ecosystem in all ramifications. Various contaminants basically hydrocarbons alter the normal structure of soil and vital soil microorganisms that aid in nutrient recycling and soil fertility. The characteristic features of the bacteria isolated from the palm oil-polluted soil sediment in this study corroborate with the report of several researchers (Jeremiah *et al.*, 2014; Jeremiah *et al.*, 2018; Imo and Ihejirika, 2021; Popoola *et al.*, 2022) who evaluated potentials of certain bacterial species in degrading complex compounds in palm oil. In this study, *Pseudomonas* species was isolated while Adegbola *et al.* (2020) and Popoola *et al.* (2022) isolated *Bacillus* species, *Micrococcus* species, *Pseudomonas*, *Aspergillus* species as palm oil effluent degraders. The ability of the bacterial isolates to utilize various sugars and sugar alcohol such as starch, glucose, maltose, dulcitol, inositol, and xylitol could be attributed to their high degradative potentials. This observation agrees with the findings of several researchers (Popoola and Onilude, 2017; Jeremiah *et al.*, 2018; Popoola *et al.*, 2022) who documented that *Bacillus* species utilize breakdown carbohydrate as source of carbon and energy for metabolism. The increase in the optical diameter of the bacterial isolates as the degradation day increases could be attributed to their ability to utilize the products of degradation as source of energy and carbon for optimum proliferation. This observation corresponds to the report of Kwute and Ijah (2014) that investigated potentials of microorganisms in degrading palm oil effluent and recorded a high number of the isolates at the highest day of degradation. The loss in weight of the hydrocarbon as the degradation day increases could be attributed to biodegradation of the bacterial isolates where the major components are utilized as source of energy and carbon. This observation is in line with the reports of several researchers (Mohammadreza and Soheila, 2014; Jeremiah *et al.*, 2014; Kwute and Ijah, 2014) who evaluated biodegradative potentials of different microorganisms.

CONCLUSION

This study has investigated the ex-situ assessment of biodegradative potential of bacteria isolated from diesel contaminated sites and revealed that *Pseudomonas* species had ability to degrade complex compounds in palm oil effluent as energy and carbon sources. The study also showed that biodegradation increases with time, and there is always reduction in the weight of hydrocarbon as biodegradation increases. Therefore, *Pseudomonas* species can be optimized for environmental sanitation of palm oil effluent-polluted soil for optimum productivity.

REFERENCES

1. Abdurahman, N. H., Rosli, Y. M., and Azhari, N. H. (2013). The performance evaluation of anaerobic methods for Palm Oil Mill Effluent (POME) treatment: A review. *International perspectives on water quality management and pollutant control* 1:88- 106.
2. Adegbola, G.M., Adeoye, A. and Simeon, O. (2020). A Review of Biodegradation as a panacea for Palm Oil Mill Effluents (POME) Pollution. *International Journal of Current Microbiology and Applied Sciences* 9(11):303.
3. Affandi, I. E., Suratman, N. H., Abdullah, S., Ahmad, W. A., and Zakaria, Z. A. (2014). Degradation of oil and grease from high-strength industrial effluents using locally isolated aerobic biosurfactant-producing bacteria. *International Biodeterioration and Biodegradation* 95: 33-40.
4. Agamuthu, P., Tan, E. L., and Ahmad, A., Bhat, A. H., Buang, A., Shah, S. M. U., and Afzal, M. (2019). Biotechnological application of microalgae for integrated palm oil mill effluent (POME) remediation: a review. *International Journal of Environmental Science and Technology* 16(3):1763-1788.
5. Aresta, M., Acquaviva, M. I., Baruzzi, F., Noce, R. L., Matarante, A., Narracci, M., .. and Cavallo, R. A. (2010). Isolation and characterization of polyphenols-degrading bacteria from olive-mill wastewaters polluted soil. *World Journal of Microbiology and Biotechnology* 26(4): 639-647
6. Awotoye, O.O., Dada, A.C., and Arawomo, G.A.O. (2011). Impact of palm oil processing effluent discharging on the quality of receiving soils and rivers in south Western Nigeria. *Journal of Applied Sciences Research* 7: 111-118.
7. Azmi, N. S. and Yunus, K. F. M. (2014). Wastewater Treatment of Palm Oil Mill Effluent (POME) by Ultrafiltration Membrane Separation Technique Coupled with Adsorption Treatment as Pre-Treatment. *Agricultural Science Procedure* 2:257–264.
8. Bala, J.D. (2016). Aerobic treatment and biodegradation of palm oil mill effluent by indigenous microorganisms. PhD Dissertation. Environmental Technology Division, School of Industrial Technology, Universiti Sains Malaysia.
9. Bambang, T., Vivian, W. and Yoshimasa, T. (2012). Methane emission from digestion of palm oil mill effluent (POME) in a thermophilic anaerobic reactor. *International Journal of Science and Engineering* 3(1): 32-35.
10. Bashir, M. J. K., Mau Han, T., Jun Wei, L., ChoonAun, N. and Abu Amr, S. S. (2016). Polishing of Treated Palm Oil Mill Effluent (POME) from Ponding System by Electrocoagulation Process. *Water Science Technology* 73:2704– 2712
11. Chin, Y. H., Sin, J. C., Lam, S. M. and Mohamed, A. R. (2019). Preparation of Nb₂O₅-decorated hierarchical porous ZnO microspheres with enhanced photocatalytic degradation of palm oil mill effluent. *Journal of Materials Science: Materials in Electronics* 30(2) 1739-1750.
12. Dhouib, A., Ellouz, M., J Gamaralalage, D., Sawai, O.s and Nunoura, T. (2019). Degradation Behavior of Palm Oil Mill Effluent in Fenton Oxidation. *J. Hazard. Mater.* 364, 791–799.
13. Imo, E.O. and Ihejirika, C.E. (2021). Microbial load and biodegradation of palm oil mill effluent (POME) by microorganisms at different stages of discharge. *International Journal of Environmental Quality* 44: 9 – 17
14. Jeremiah, D. B., Japareng, L., Adel, A.A. and Kaizarh., N. I. (2018). Microbiota of Palm Oil Mill Wastewater in Malaysia. *Tropical Life Sciences Research* 29(2):131–163
15. Jeremiah, D.B., Japareng, L. and Norli, I. (2014). Biodegradation of palm oil mill effluent (POME) by bacterial. *International Journal of Scientific and Research Publications* 3(4):1 – 10.

16. Kwute, O. L. and Ijah, U. J. J. (2014). Bioremediation of palm oil mill effluent (POME) polluted soil using microorganisms found in organic waste. *The International Journal of Biotechnology* 3(3):32 – 46.
17. Mohammadreza, S. and Soheila, M. (2014). Enhancement of Biodegradation of Palm Oil Mill Effluents by Local Isolated Microorganisms. *International Scholarly Research Notices* 1: 10
18. Obahiagbon, F.I. (2012). A Review: Aspects of the African Oil Palm (*Elaeis guineensis* Jacq.). *American Journal of Biochemistry and Molecular Biology* 1-14
19. Popoola, B.M. and Onilude, A.A. (2017). Microorganisms Associated with Vegetable Oil Polluted Soil. *Advances in Microbiology* 7: 377 – 386.
20. Popoola, B.M., Famakinwa, P.B. and Adeyemi, O.A. (2022) Isolation of Microorganisms Associated with Palm Oil Contaminated Soil. *Journal of Environmental Pollution and Control* 5(2): 204